

Battery nutrunner

DA2

The next generation – for a smarter performance



Construction



Wind power



Steel construction



Transport sector



Oil & gas industry



Engineering

One nutrunner – three variants

Improved performance through advanced engineering and optimisation of all mechanical components

DA2*power*

The strong allrounder.

Proven Plarad tech in a new guise. Powerful and reliable, it can handle any bolting challenge and you can even upgrade it to the variant models *docu* and *control*.

DA2*docu*

Precision tool – for demanding work.

On top of the *DA2power's* extensive features, the *DA2docu* saves bolting results together with their location and sends them to a smart device by WiFi.



DA2*control*

High-end tool for the toughest jobs.

Besides offering the same strong performance as the *DA2docu*, the *DA2control* also comes with torque-and-rotary-angle mode and inspection mode for tightened bolts – worldwide unique.



Highlights of the new high-performance **DA2power** series

Quick to use and adaptable thanks to 4-speed gearbox

Battery at full charge in less than 30 minutes thanks to high-performance charger

Reaction arm disengages automatically when bolting is complete to improve safety and ergonomics

Battery charge levels easy to track

High-power unfastening settings for those extra-stubborn bolts

Reliable Fein drive and battery technology guarantees quality and worldwide availability

The patented articulation lets you pivot the drive through 360° without intermittent locking


Automatic locking when traction applies protects your personnel and make operation more comfortable than ever

Nickel-coated surface prevents corroded gearing

Robust trolley makes tool easy to transport

All DA2power models can be upgraded to DA2docu or DA2control. If you need your nutrunner to do more, send it in for reprogramming and you'll be ready for whatever industry 4.0 throws your way.

Model overview



Type	Torque range	A	B	Ø C	Weight	Drive	Base model
		mm	mm	mm			
DA2-05power	130 – 550 Nm	365	185	68,5	5,10	¾"	86070
DA2-10power	180 – 1000 Nm	365	185	68,5	5,90	¾"	86080
DA2-20power	220 – 2000 Nm	405	185	80	5,90	1"	86090
DA2-30power	330 – 3000 Nm	405	185	80	6,20	1"	86900
DA2-36power	380 – 3600 Nm	405	185	80	6,20	1"	86110
DA2-48power	500 – 4800 Nm	436	185	86	8,15	1½"	86120
DA2-80power	700 – 8000 Nm	521	185	101	12,50	1½"	86130

Repeat accuracy: ≤ 4%, dependent on the bolted joint. Regardless of the torque, the repeat accuracy depends on the individual bolted joint and therefore has to be determined for the specific bolting application.
Weight without reaction arm and battery pack.



Phone: +49 (0) 2245 62-0

@ email: info@plarad.de

Web: www.plarad.de



... a reliable connection!